

N3066 (p1): timespec::tv_nsec

timespec::tv_nsec is too wide and unsatisfiable by some architectures.
Relaxing the type can alleviate this.

наб

N3066 (p1): `timespec::tv_nsec`

`timespec::tv_nsec` is too wide and unsatisfiable by some architectures.
Relaxing the type can alleviate this.

наб

Document #: 3066
Date: 2022-12-14
Revisions: [N2878](#)
Project: Programming Language C
Reply-to: наб <nabijaczleweli@nabijaczleweli.xyz>

1. The issue

The current wording in the current draft C2X standard [N2731](#) from 7.27.1.4 is:

The range and precision of times representable in `clock_t` and `time_t` are implementation-defined. The `timespec` structure shall contain at least the following members, in any order. The semantics of the members and their normal ranges are expressed in the comments.³⁴²⁾

```
time_t tv_sec; // whole seconds -- ≥ 0
long tv_nsec; // nanoseconds -- [0, 999999999]
```

However, this presents a small set of problems:

- a) the minor: this is a hold-over from I16L32 architectures, and on LP64 architectures `longs` are way too big, and
- b) the major: there are existing implementations which *cannot* conform to this, due to ABI requirements.

2. Examples

Under Linux®, on the [X32](#) ABI, the kernel's `struct timespec` is invariably

```
struct timespec {
    time_t tv_sec;
    long tv_nsec;
};
```

under the *kernel ABI*: the LP64 AMD64. This means that from the ILP32 userspace, it looks like this:

```
struct timespec {
    time_t tv_sec;
    int64_t tv_nsec;
};
```

The shortest available `int64_t` is `long long`, and the libc *must* expose a kernel-ABI-compatible `timespec` — a pickle indeed!

3. Proposed wording

3.1. 7.27.1.4

The range and precision of times representable in `clock_t` and `time_t` are implementation-defined. The `timespec` structure shall contain at least the following members, in any order. The semantics of the members and their normal ranges are expressed in the comments.³⁴²⁾

```
time_t tv_sec; // whole seconds -- ≥ 0
long tv_nsec; // nanoseconds [0, 999999999]
/* see below */ tv_nsec; // nanoseconds -- [0, 999999999]
```

The `tv_nsec` member shall be of an implementation-defined signed integer type capable of representing the range [0, 999999999].

The `tm` structure shall... [rest of section unchanged]

4. Rationale

Being strictly additive, this changes nothing on already-conforming implementations: `tv_nsec` can simply continue to be a `long`.

However, this enforces the need to cast `tv_nsec` to a concrete type for formatting and other processing.

5. References

The current Linux ABI `timespec` situation: <https://sourceware.org/pipermail/libc-alpha/2021-December/133702.html> — this is part of a larger thread born out of an attempt to accurately describe `time-spec::tv_nsec` as part of Linux man-pages' `system_data_types(7)`: <https://lore.kernel.org/linux-man/ec1dcc655184f6cdaae40ff8b7970b750434e4ef.1638123425.git.nabijaczleweli@nabijaczleweli.xyz/T/>

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Contents

1. The issue 1

2. Examples 1

3. Proposed wording 1

 3.1. 7.27.1.4 1

4. Rationale 2

5. References 2